



Main Specifications

Product Description	ADTRAN NetVanta 1335 - router
Device Type	Router + 24-port switch (integrated)
Form Factor	External - modular - 1U
Dimensions (WxDxH)	17.2 in x 9.3 in x 1.7 in
Weight	7 lbs
Processor	Freescape 266 MHz
RAM	128 MB
Flash Memory	32 MB
Routing Protocol	OSPF, RIP-1, RIP-2, BGP, IGMPv2, PIM-SM, static IP routing, GRE
Data Link Protocol	Ethernet, ATM, Fast Ethernet, HDLC, Frame Relay, PPP, MLPPP, FRF.12
Network / Transport Protocol	UDP/IP, IPSec, PPPoE, PPPoA, PAP
Remote Management Protocol	SNMP 3, HTTP
VoIP Functionality	VoIP gateway
VoIP Protocols	SIP
Features	ADTRAN OS , modular design, firewall protection, switching, layer 3 switching, DHCP support, NAT support, hardware encryption, VPN, NAPT support, trunking, MPLS support, VLAN support, auto-uplink (auto MDI/MDI-X), Syslog support, DoS attack prevention, content filtering, packet filtering, ALG support, port mirroring, DiffServ support, manageable, stackable, Weighted Round Robin (WRR) queuing, firmware upgradable, integrated CSU/DSU, Low-latency queuing (LLQ), Weighted Fair Queuing (WFQ), wall mountable, SMTP traffic control, Quality of Service (QoS)
Compliant Standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1ad, IEEE 802.1ab (LLDP)
Power	AC 120/230 V (50/60 Hz)
Manufacturer Warranty	5 years warranty

General

Device Type	Router
Form Factor	External - modular - 1U
Installed Modules Qty (Max)	0 (installed) / 1 (max)
Width	17.2 in
Depth	9.3 in

Height	1.7 in
Weight	7 lbs
Processor	
Type	Freescape 266 MHz
Memory	
RAM	128 MB
Flash Memory	32 MB
Networking	
Connectivity Technology	Wired
Integrated Switch	24-port switch
Data Link Protocol	Ethernet, ATM, Fast Ethernet, HDLC, Frame Relay, PPP, MLPPP, FRF.12
Switching Protocol	Ethernet
Network / Transport Protocol	UDP/IP, IPSec, PPPoE, PPPoA, PAP
Routing Protocol	OSPF, RIP-1, RIP-2, BGP, IGMPv2, PIM-SM, static IP routing, GRE
Remote Management Protocol	SNMP 3, HTTP
Performance	Switching capacity : 8.8 Gbps
Capacity	VPN tunnels : 500
Status Indicators	Link activity, power, test mode, status, alarm
Features	Modular design, firewall protection, switching, layer 3 switching, DHCP support, NAT support, hardware encryption, VPN, NAPT support, trunking, MPLS support, VLAN support, auto-uplink (auto MDI/MDI-X), Syslog support, DoS attack prevention, content filtering, packet filtering, ALG support, port mirroring, DiffServ support, manageable, stackable, Weighted Round Robin (WRR) queuing, firmware upgradable, integrated CSU/DSU, Low-latency queuing (LLQ), Weighted Fair Queuing (WFQ), wall mountable, SMTP traffic control, Quality of Service (QoS)
Compliant Standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1ad, IEEE 802.1ab (LLDP)
IP Telephony	
VoIP Functionality	VoIP gateway
VoIP Protocols	SIP
Expansion / Connectivity	
Expansion Slots Total (Free)	1 (1) x CompactFlash Card 1 (1) x expansion slot 2 (2) x SFP (mini-GBIC)
Interfaces	2 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x management - console - 9 pin D-Sub (DB-9) 24 x network / power - Ethernet 10Base-T/100Base-TX - RJ-45

Miscellaneous	
Encryption Algorithm	DES, Triple DES, RSA, MD5, AES, SSL, SHA-1
Authentication Method	SecurID, Secure Shell (SSH), RADIUS, PAP, CHAP, TACACS+
Compliant Standards	CSA, cUL, UL 1950, FCC Part 68, RoHS, WEEE, FCC Part 15 A
Power	
Power Device	Power supply - internal
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	36 Watt
Software / System Requirements	
OS Provided	ADTRAN OS
Manufacturer Warranty	
Service & Support	5 years warranty
Service & Support Details	Limited warranty - 5 years
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	122 °F
Humidity Range Operating	0 - 95%